REMARKS

Applicants have replaced the abstract and amended the claims to improve the claim language and to eliminate improper claim dependency. Applicants have also amended the specification to correct some headings and to rearrange the specification in accordance with usual U.S. practice. The revisions to Table 2 correct obvious typographical errors in identifying the examples tested. Applicants attach a clean copy of the application as amended above in the third Appendix. No new matter has been added, nor has the claim scope been narrowed by these amendments.

Early action allowing claims 1-9 is solicited.

In the event that the transmittal letter is separated from this document and the Patent and Trademark Office determines that an extension and/or other relief is required, applicant petitions for any required relief including extensions of time and authorizes the Commissioner to charge the cost of such petitions and/or other fees due in connection with the filing of this document to **Deposit Account No. 03-1952** referencing docket no. 358362011400.

By:

Respectfully submitted,

Dated: September 18, 2006

Barry E. Bretschneider Registration No. 28,055

Morrison & Foerster LLP 1650 Tysons Boulevard, Suite 300 Mclean, Virginia 22102

Telephone: (703) 760-7743 Facsimile: (703) 760-7777

[0029]

Table 2

swelling ratio product thickness thermal shrinkage (%) thermal shrinkage (%)	product thickness thermal shrinkage (%)	thickness thermal shrinkage (%)	thermal shrinkage (%)				thermal shrink	shrink	ag	e (%)		Processing	Processing thickness
base sealing width X variation rate right Center left end right end layer (mm)	takeout variation rate right (mm)	variation rate right (%)	right end		Center left end right en	left end right en	right en	70	center left end	left end	gloss (%)	applica- ve	variation rate Z (%)
	6200 6.2 0.3 0.1 0.4	6.2 0.3 0.1 0.4	0.3 0.1 0.4	0.1 0.4	0.4	0.4 3.2	3.2	<u> </u>	3.8	3.1	130	0	6.0
7.3 0.5 0.4 0.1	6200 7.3 0.5 0.4 0.1	7.3 0.5 0.4 0.1	0.5 0.4 0.1	0.4 0.1	0.1	0.1 2.9	2.9		3.3	3.8	127	0	6.4
1.31 1.47 6200 15.5 -0.1 0.1 0.4 3.2	6200 15.5 -0.1 0.1 0.4	15.5 -0.1 0.1 0.4	-0.1 0.1 0.4	0.1 0.4	0.4	D .	3.	2	2.2	1.2	120	×	24.7
1.31 1.24 6200 20.0 1.0 0.7 0.5 2	6200 20.0 1.0 0.7 0.5	20.0 1.0 0.7 0.5	1.0 0.7 0.5	0.7 0.5	0.5	į		2.5	4.1	3.6	115	×	26.3